

IBC4M-EXIR



IBC4M-EXIR

4 MegaPixel IP 4mm Fixed Lens, White Housing, POE/12VDC

4MP HD²
2688 x 1520

4MP IP Bullet Camera - ONVIF

Megapixel 4mm Fixed HD Lens



2688x1520p IP Camera

*4MP (MegaPixel) IP Bullet Camera provides superior video quality for surveillance video systems

* POE (Power Over Ethernet) provides simplified installation by running power on the Cat5/6

* EXIR provides next-gen IR light that provides a smoother and width range of night vision.

* True 120dB WDR, BLC, HDR

2688x1520p

OSD via IP

True WDR

4mm Lens

Features

- 4MP 1/2.8" Progressive Scan CMOS Sensor
- Megapixel Fixed HD Lens
- 2688x1520p IP Network Camera
- 0.01Lux @ F1.2 (AGC On), 0Lux IR On
- EXIR LED
- Sunshield
- AGC, BLC, 3D-DNR
- 120dB True WDR
- POE or 12VDC

Connections

RJ45 8P8C



POWER 12VDC



Dimensions (Unit:mm)

Specifications

Imaging Sensor	1/2.8" Progressive Scan Megapixel CMOS Sensor
HD IP Scanning System	2688x1520p Progressive Scan
Analog Scanning System	N/A
Number of Active Pixels	2688(H)x 1520(V) NTSC
Total Number of pixels	2688(H)x 1520(V) NTSC
H.264 Profile	Main Profile
Stream Profiles	H.264 / MJPEG
Bit Rate	32 Kbps ~ 16 Mbps
Min. Illumination	0.01 Lux @ F1.2 (AGC on), 0.0 Lux IR On
Lens	4mm Fixed Megapixel Lens
Electronic Shutter Speed	1/30-100,000sec
White Balance	AWB1, Locked WB, Incandescent, Warm, Natural, & Fluorescent
Backlight Compensation	WDR, BLC, HLC, OFF
WDR	0-100, OFF
AGC	0-100, OFF
Adjust	Brightness, Hue, Contrast, Sharpness
Language	English
Day & Night	Day, Night, Auto, Schedule
2D/3D-NR	3D-DNR
Event - Motion	On, Dynamic, Schedule, Sensitivity, Off
Event - Video Tampering	On, Sensitivity, Schedule, Off
Event - Exception	HDD Full, HDD Error, Network Disconnected, IP Conflict, Illegal Login
Event - Line Crossing Detection	On, A <-> B, A -> B, B <- A, Sensitivity, Schedule
Event - Intrusion Detection	On, Threshold, Sensitivity, Percentage, Schedule
D - EFFECT	Mirror / Rotate / Scene Mode / Video Standard / Capture Mode
IR LED	EXIR LED
Construction	High Impact IK10 Polycarbonate Dome & Die Cast Body
Operation Temperature	-30°C - 60°C (-22°F - 140°F), Humidity 95% or Less (non-condensing)
Storage Temperature	-30°C - 60°C (-22°F - 140°F)
Humidity	0% to 95%
Supplied Voltage	DC12V±10% or POE (Power Over Ethernet) 48V
Power Consumption	Max 7.5w (IR On)
Dimension (H x W x L)	85.1mm x 86.4mm x 299.7mm (3.35" x 3.4" x 11.8") Height x Width x Length
Weight	700g

*Design and specifications are subject to change without notice.