

IBC4M-EXIR



ARMIX
CCTV

IBC4M-EXIR-XX

4 MP IP EXIR Low Light Bullet Camera



H.264
AVC
Advanced video coding

4 MP
2688x1520 Resolution

IP66 Weatherproof Bullet Camera
H.264 Internal Compression Codec Processor

H.264 / MJPEG

4MP Resolution

20FPS @ 4MP

POE Ready

Features

- Supports both H.264 & MJPEG video compression
- Bullet-type enclosure
- Integrated sun shield to prevent lens glare
- High quality metal housing with integrated weather seal to maintain IP66 rating
- 3-Axis manually adjustable lens for tilt, rotation, and horizontal position
- Integrated motion detection and privacy windows
- EXIR LEDs provide smooth, clear IR light for B/W conditions for less IR blooming / white out
- Compatible with Armix Connect integration
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Wall, ceiling, and back box mounts available
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	2688x1520p (4MP)
		Optional Resolutions	1920x1080, 1280x720
	Sub	Maximum Resolution	640x360
		Optional Resolutions	352x240
Audio	Input & Output		-
	Audio Codec		-
Alarm	Input		-
	Output		-
Serial	RS-232C		-
	RS-485		-
Recording	Compression		H.264+ / H.264 / MJPEG
	Max Resolution		4MP
	Bit Rates Profiles		Constant or Variable
	Max Frames Per Second		20FPS (4MP) 30FPS (2MP or Less)
	Quality Settings		6 Settings (Lowest to Highest)
	Video Streams		Main and Sub
Lens	Types		4mm 6mm 12mm
	Shutter Time		1/3s ~ 1/100,000s
	Angle of View		83° 55° 25°
Day & Night	Lux	IR Off	0.01 Lux (F1.2, AGC On)
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR		Digital
	BLC		Yes
	DNR		3D-DNR
Power	Accepted Inputs		POE or 12VDC
Temperature	Operation Temperature		-30-60C / -22-140F (Humidity 90% or Less)
Weight	Unit Weight		2.65 lbs
Dimension	Unit Dimension (H x W x D)		3.4" x 3.4" x 11.8"

Specifications subject to change without notice