

IBC4MV



ARMIX
CCTV

IBC4MV

4 MP IP Motorized Varifocal Bullet Camera



H.264
AVC
Advanced video coding

4 MP
2688x1520 Resolution

IP66 Weatherproof Bullet Camera
H.264 Internal Compression Codec Processor

H.264 / MJPEG

4MP Resolution

20FPS @ 4MP

POE Ready

Features

- Supports both H.264 & MJPEG video compression
- Bullet-type enclosure
- Integrated sun shield to prevent lens glare
- High quality metal housing with integrated weather seal to maintain IP66 rating
- Motorized varifocal lens can be controlled using PTZ function from internet browser
- Integrated motion detection and privacy windows
- Audio I/O and alarm I/O break out
- Compatible with Armix Connect integration
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Includes camera back box with 2 points of entry
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	2688x1520p (4MP)
		Optional Resolutions	1920x1080, 1280x720
	Sub	Maximum Resolution	640x360
		Optional Resolutions	352x240
Audio	Input & Output	1	
	Audio Codec	1	
Alarm	Input	1	
	Output	1	
Serial	RS-232C	-	
	RS-485	-	
Recording	Compression	H.264+ / H.264 / MJPEG	
	Max Resolution	4MP	
	Bit Rates Profiles	Constant or Variable	
	Max Frames Per Second	20FPS (4MP) 30FPS (2MP or Less)	
	Quality Settings	6 Settings (Lowest to Highest)	
	Video Streams	Main and Sub	
Lens	Types	2.8-12mm	
	Shutter Time	1/3s ~ 1/100,000s	
	Angle of View	33.8-112°	
Day & Night	Lux	IR Off	0.01 Lux (F1.2, AGC On)
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR	Digital	
	BLC	Yes	
	DNR	3D-DNR	
Power	Accepted Inputs	POE or 12VDC	
Temperature	Operation Temperature	-30-60C / -22-140F (Humidity 90% or Less)	
Weight	Unit Weight	1.5 lbs	
Dimension	Unit Dimension (L x W x D)	3.7" x 4.1" x 10.2"	

Specifications subject to change without notice