

IPTZ5M-30XIR



ARMIX
CCTV

IPTZ5M-30XIR

5 MP IP Pan Tilt Zoom Camera with 30X Zoom & IR



**Pan Tilt Zoom IP66 Weatherproof Dome
H.265 Internal Compression Codec Processor**

H.265 / H.264 / MJPEG

5MP Resolution

20FPS @ 5MP

POE+ Ready

Features

- Supports both H.264 & H.265 video compression
- 30X optical zoom motorized lens
- Manual pan speed 0.1°~160°/sec | Preset pan speed 240°/s
- Manual tilt speed 0.1°~120°/sec | Preset pan speed 200°/sec
- Fully motorized pan, tilt, and zoom controlled via web interface, DVR/NVR, or Armix V2 app
- Endless 360° Pan; Tilt -15°~90° (Auto Flip)
- Audio I/O and alarm I/O break out
- Built-in variable output IR, 450ft Max.
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Wall, ceiling, and back box mounts available
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	2592x1944p (5MP)	
		Optional Resolutions	1920x1080	
	Sub	Maximum Resolution	640x360	
		Optional Resolutions	352x240	
Audio	Input & Output	1/1		
	Audio Codec	G.711		
Alarm	Input	2		
	Output	1		
Serial	RS-232C	-		
	RS-485	-		
Recording	Compression	H.265 / H.264+ / H.264 / MJPEG		
	Max Resolution	5MP		
	Bit Rates Profiles	Constant or Variable		
	Max Frames Per Second	30FPS (5MP), 60FPS (2MP)		
	Quality Settings	6 Settings (Lowest to Highest)		
	Video Streams	Main and Sub		
Lens	Types	5.9 ~ 177mm		
	Shutter Time	1/3s ~ 1/100,000s		
	Angle of View	51.3 ~ 2.7°		
Day & Night	Lux	IR Off	0.005 Lux (F1.5, AGC On) - Color	
		IR On	0 Lux	
	ICR	Mode	Automatic, Day, Night, Schedule Switch	
		Sensitivity	Selectable (0-7)	
Image	WDR	Digital		
	BLC	Yes		
	DNR	3D-DNR		
Power	Accepted Inputs	High Power POE or 24VAC		
Temperature	Operation Temperature	-30-60C / -22-140F (Humidity 90% or Less)		
Weight	Unit Weight	9.9 lbs		
Dimension	Unit Dimension (Ø x D)	8.7" x 13.9"		

Specifications subject to change without notice