

IPTZ8M-36XIR



ARMIX
CCTV

IPTZ8M-36XIR

8 MP IP Pan Tilt Zoom Camera with 36X Zoom & IR



**Pan Tilt Zoom IP67 Weatherproof Dome
H.264 Internal Compression Codec Processor**

H.264 / MJPEG

8MP Resolution

24FPS @ 8MP

POE+ Ready

Features

- Intelligent 3-D Positioning - Auto Tracking
- 36X optical / 16X digital zoom motorized lens
- Manual pan speed 0.1°~160°/sec | Preset pan speed 240°/s
- Manual tilt speed 0.1°~120°/sec | Preset pan speed 200°/sec
- Fully motorized pan, tilt, and zoom controlled via web interface, DVR/NVR, or Armix V2 app
- Endless 360° Pan; Tilt 20°~90° (Auto Flip)
- Audio I/O and alarm I/O break out
- Built-in variable output IR, 650ft Max.
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Wall, ceiling, and back box mounts available
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	4096x2160p (8MP)
		Optional Resolutions	3840x2160p, 2560x1440, 1920x1080
	Sub	Maximum Resolution	640x360
		Optional Resolutions	352x240
Audio	Input & Output		1/1
	Audio Codec		G.711
Alarm	Input		1
	Output		1
Serial	RS-232C		-
	RS-485		-
Recording	Compression		H.264+ / H.264 / MJPEG
	Max Resolution		8MP
	Bit Rates Profiles		Constant or Variable
	Max Frames Per Second		24FPS 30FPS
	Quality Settings		6 Settings (Lowest to Highest)
Lens	Types		5.7 ~ 205mm
	Shutter Time		1/3s ~ 1/100,000s
	Angle of View		56.8 ~ 2.0°
Day & Night	Lux	IR Off	0.02 Lux (F1.2, AGC On) - Color
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR		True 120dB
	BLC		Yes
	DNR		3D-DNR
Power	Accepted Inputs		High Power POE or 24VAC
Temperature	Operation Temperature		-30-60C / -22-140F (Humidity 90% or Less)
Weight	Unit Weight		17.6 lbs
Dimension	Unit Dimension (Ø x D)		10.5" x 17.1"

Specifications subject to change without notice