

ITC4M Series



ARMIX
CCTV

ITC4M-XX

4 MP IP Turret Camera



*Pre-2018 Model

Features

- Supports H.264 & MJPEG video compression
- Metal housing with 2nd gen EXIR IR LEDs
- Clean, streamlined appearance
- High quality metal housing with integrated weather seal to maintain IP66 rating
- Fully adjustable design
- Integrated motion detection and privacy windows
- Compatible with Armix Connect integration
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Wall, ceiling, and back box mounts available
- 2 Year Warranty

Connectors



IP66 Weatherproof Housing
H.264 Internal Compression Codec Processor

H.264+ / H.264 / MJPEG

4MP Resolution

20FPS @ 4MP

POE Ready

Video	Main	Maximum Resolution	2688x1520p (4MP)
		Optional Resolutions	1920x1080
	Sub	Maximum Resolution	640x360
		Optional Resolutions	352x240
Audio	Input & Output		-
	Audio Codec		-
Alarm	Input		-
	Output		-
Serial	RS-232C		-
	RS-485		-
Recording	Compression		H.264+ / H.264 / MJPEG
	Max Resolution		4MP
	Bit Rates Profiles		Constant or Variable
	Max Frames Per Second		20FPS (4MP) 30FPS (2MP)
	Quality Settings		6 Settings (Lowest to Highest)
	Video Streams		Main and Sub
Lens	Types		2.8mm 4mm 6mm
	Shutter Time		1/3s ~1/100,000s
	Angle of View		106° (2.8mm) 83° (4mm) 56° (6mm)
Day & Night	Lux	IR Off	0.01 Lux (F1.2, AGC On)
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR		True 120dB
	BLC		Yes
	DNR		3D-DNR
Power	Accepted Inputs		POE or 12VDC
Temperature	Operation Temperature		-30-60C / -22-140F (Humidity 90% or Less)
Weight	Unit Weight		1.5 lbs
Dimension	Unit Dimension (Ø x D)		5.0" x 3.8"

Specifications subject to change without notice