

IVD1536 Series



ARMIX
CCTV

IVD1536-XX

3 MP IP Vandal Resistant Dome Camera



H.264
AVC
Advanced video coding

3 MP
2048x1536 Resolution

**IK10 Vandal Resistant + IP66 Weatherproof Dome
H.264 Internal Compression Codec Processor**

H.264 / MJPEG

3MP Resolution

20FPS @ 3MP

POE Ready

Features

- Supports both H.264 & MJPEG video compression
- Vandal resistance IK10 dome
- Professional appearance with improved, miniature LEDs in a new 3-axis bezel
- High quality metal housing with integrated weather seal to maintain IP66 rating
- 3-Axis manually adjustable lens for tilt, rotation, and horizontal position
- Integrated motion detection and privacy windows
- Audio I/O and alarm I/O break out (Optional)
- Compatible with Armix Connect integration
- ONVIF compatible
- POE (Power-over-ethernet) Ready
- Wall, ceiling, and back box mounts available
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	2048x1536p (3MP)
		Optional Resolutions	1920x1080, 1280x720
	Sub	Maximum Resolution	704x480
		Optional Resolutions	640x480, 352x240, 320x240
Audio	Input & Output		-
	Audio Codec		-
Alarm	Input		-
	Output		-
Serial	RS-232C		-
	RS-485		-
Recording	Compression		H.264+ / H.264 / MJPEG
	Max Resolution		3MP
	Bit Rates Profiles		Constant or Variable
	Max Frames Per Second		20FPS (3MP), 30FPS (2MP and Below)
	Quality Settings		6 Settings (Lowest to Highest)
	Video Streams		Main and Sub
Lens	Types		2.8mm 4mm
	Shutter Time		1/3s ~ 1/100,000s
	Angle of View		98° (2.8mm) 76° (4mm)
Day & Night	Lux	IR Off	0.01 Lux (F1.2, AGC On)
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR		Digital
	BLC		Yes
	DNR		3D-DNR
Power	Accepted Inputs		POE or 12VDC
Temperature	Operation Temperature		-30-60C / -22-140F (Humidity 90% or Less)
Weight	Unit Weight		1.1 lbs
Dimension	Unit Dimension (Ø x D)		4.4" x 3.2"

Specifications subject to change without notice