

TBC5MV



ARMIX
CCTV

TBC5MV

5 MP TVI Motorized Varifocal Bullet Camera



5 MP
2560x1944 Resolution

IP67 Weatherproof Bullet Housing
Motorized 2.8-12mm Varifocal Lens

Turbo HD

5MP Resolution

D-WDR

12VDC / 24VAC

Features

- Works with TX2-Series DVRs
- Motorized varifocal lens using PTZ OSD controls
- Professional appearance with improved 2nd generation EXIR IR LEDs
- High quality metal housing with integrated weather seal to maintain IP66 rating
- 3-Axis manually adjustable mount for tilt, rotation, and horizontal position
- OSD menu accessible through DVR
- 12VDC / 24VAC Power Requirement
- Back box mounts available
- 2 Year Warranty

Connectors



Video	Main	Maximum Resolution	2560x1944p (5MP)
		Synchronization	Internal
	CBVS	Maximum Resolution	-
		Synchronization	-
Audio	Input & Output		-
	Audio Codec		-
Alarm	Input		-
	Output		-
Serial	RS-232C		-
	RS-485		-
Recording	Effective Pixels		2560 H x 1944 V
	Max Resolution		5MP
	Encoding		Turbo HD (TVI)
	Max Frames Per Second		20FPS
	Format		NTSC
	Video Streams		Primary Only
Lens	Types		2.8-12mm
	Shutter Time		1/30 ~ 1/50,000s
	Angle of View		102° - 31°
Day & Night	Lux	IR Off	0.008 Lux (F1.2, AGC On)
		IR On	0 Lux
	ICR	Mode	Automatic, Day, Night, Schedule Switch
		Sensitivity	Selectable (0-7)
Image	WDR		Yes
	BLC		Yes
	DNR		3D-DNR
Power	Accepted Inputs		12VDC 24VAC
Temperature	Operation Temperature		-40-60C / -40-140F (Humidity 90% or Less)
Weight	Unit Weight		1.98 lbs
Dimension	Unit Dimension (H x W x D)		3.6" x 3.3" x 10.6"

Specifications subject to change without notice